

## **High Speed Controller Card**



## **Applications**

- Distributed Data Acquisition Systems
- Safety of Flight Telemetry
- On-board Recording
- Real-time Data Display and Analysis

## **Features**

- Data Formatter for the CDAU-2020
- Houses the System Format EEPROM
- Controls PCM Data Rate Parameters
- Bit rates up to 20 Mbps or 1.666 Megasamples per second (whichever is
- Bits-Per-Word settings of 10, 12, 14 or 16
- PCM Format Capabilities
- Supports up to eight (8) independent PCM formats externally strappable
- Each format can be up to 512 words per minor frame and up to 256 sub-
- Uses "True Subcommutation" sublists to conserve memory space
- Provides AIC-200X (composite) data outputs
- One (1) Primary PCM (RS-422) at up to 20 Mbps with programmable PCM coding
- Three (3) NRZ-L PCM (RS-422)
- One (1) NRZ- PCM (TTL)
- One (1) Filtered PCM w/automatic filter cutoff based on system bit rate.
- Supports System Simultaneous Sampling, Time Code and Calibration Enable/Disable
- Programmable using TTCWare™ software application

## **Description**

The HSC-400 provides the data formatter function for the CDAU-2020 Airborne Instrumentation Controller. This card must be installed in slot #1 in order for the CDAU-2020 to function properly. The card houses the system EEPROM device that regulates the PCM sampling formats and all associated parameters. In addition the card generates the support signals needed to support Simultaneous Sampling, IRIG Time Code, and signal conditioning calibration. The card also provides a number of buffered composite data output streams representing the entire data set acquired by the unit and associated remote units.



**HSC-400 Datasheet** 

©2015 Teletronics - A Curtiss-Wright Company Specifications subject to change without notice. Approved for Public Release 16-S-0082





Teletronics - A Curtiss-Wright Company 15 Terry Drive, Newtown, PA 18940 phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com