

2-Channel RS-232/422 Bus Monitor Module



Applications

- Flight test instrumentation
- Ethernet-based distributed network systems
- System safety monitoring

Features

- 2 channel plug-in RS-232/422 bus monitor module for the MnHSD-2000 product
- Supports IEEE 1588 for acquisition of coherent global timing information over the network fabric
- Supports EIA RS-232 standard
- Multiple modules can be installed in an MnHSD chassis
- Fully programmable using TTCWare software application
- Two independently configured channels
- Programmable RS-232 characteristics:
 - Standard baud rates from 50 to 921,600
 - 5, 6, 7, or 8 data bits
 - 1 or 2 stop bits
 - Odd, even, or no parity
 - RS-232 or RS-422 operation

Description

The MBIM-232N is a plug-in RS-232 bus monitor module for TTC's Miniature Network High-Speed Data Acquisition unit (MnHSD-2000). It accepts two independently configured channels of RS-232 data. The MBIM-232N supports serial communications per the EIA-RS-232 standard at standard baud rates from 50 to 921,600. Timestamping is provided on a per-data-packet basis.

The captured data is available on the host encoder's data output for transmission and recording purposes.

Revision 05/13/2015

MBIM-232N Datasheet

©2015 Teletronics - A Curtiss-Wright Company
Specifications subject to change without notice.

Approved for Public Release 16-S-0233

Teletronics - A Curtiss-Wright Company
15 Terry Drive, Newtown, PA 18940
phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com



Management
System
AS9100C
ISO 9001:2008