

Miniature Ethernet Interface Module



Applications

- CAIS applications
- Distributed systems
- Time-tagging data
- Ethernet to PCM

Features

- Single Channel Ethernet Module
- Creates and outputs two independent 100% composite data output streams of Class II PCM, similar to IRIG-106 Chapter 8
- MAC supports ARP (Address Resolution Protocol) Internet Protocol
- Independently programmable PCM formats
 - Frame Size either 128 or 256 Words per Frame
 - PCM Bit-Rate programmable from 20Mbps to 157.5Kbps in 128 steps
 - Frame time enable/disable
 - Bit Mode: 20 Bit, or 24 Bit
 - Output Format: NRZ-L or RNRZ-L
 - Bus ID configuration bits
 - PCM enable/disable
 - PCM Frame Sync Char user programmable (default: 0xFAF320)
 - Time format BCD/Binary (setting applies to both channels)
- Multiple modules may be installed within a single stack

Description

The METI-201A-1 is a Miniature Ethernet Interface Module with composite data output and is a member of the MEDAU-2000, MCDAU-2000 & MWDAU-2000 product family. The module is used to create a high speed, 100% composite data output stream class II PCM similar to the IRIG-106, Chapter 8 requirements. The composite data output streams contain all Ethernet data acquired by the module. Each PCM output channel can be independently programmed to a different format and a different PCM bit-rate, up to 20Mbps. The PCM Frame Sync character for each PCM channel is user programmable (Default is 0xFAF320). The METI-201A-1 module uses large on-board SRAM's and internal FIFO's to buffer the incoming Ethernet packets. This reduces the possibility of packet drops due to buffer overflows during long periods of high-speed burst Ethernet data. The METI-201A-1 can store over 1024 entire Ethernet packets in its internal memories.

Revision 05/12/2015

METI-201A Datasheet

©2015 Teletronics - A Curtiss-Wright Company
 Specifications subject to change without notice.

Approved for Public Release 16-S-0386



CAIS
Compatible



Management
System
AS9100C
ISO 9001:2008

Teletronics - A Curtiss-Wright Company
 15 Terry Drive, Newtown, PA 18940
 phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com