


### 2-Channel LVDT/RVDT Conditioner Module



#### Applications

- Airborne instrumentation
- Position feedback
- Process control systems

#### Features

- LVDT/RVDT conditioner
- High performance ratiometric tracking linear converter
- 2-channels per module
- 14 bit resolution with over-range
- Software programmable input range
  - From 1VRMS to 10VRMS (per channel)
- Software programmable excitation source
  - Programmable frequency 400 Hz to 10 KHz
  - Programmable amplitude 2 to 6 VRMS
- User configurable wiring
  - 1 or -3: 2 or 3-wire configuration
  - 2 or -4: 2-wire configuration
- +/-0.2% system accuracy
- Microsoft Windows application software included

#### Description

The MLRV-102E is a 2-channel LVDT/RVDT signal conditioning module for use in TTC's MEDAU-2000 and MCDAU-2000 products. The module provides high performance, ratiometric tracking and linear conversion to 14 bit resolution. An over-range indicator bit is also provided. The input accepts either 2-wire (-2 or -4) or 3-wire (-1 to -4) input configurations. An AC excitation source is provided that has programmable output frequency and amplitude. The input range is software programmable from 1 VRMS to 10 VRMS. The module operates from 400 Hz to 10 KHz.

Revision 05/12/2015

#### MLRV-102E Datasheet

©2015 Teletronics - A Curtiss-Wright Company  
 Specifications subject to change without notice.

Approved for Public Release 16-S-0544



CAIS  
Compatible



Management  
System  
AS9100C  
ISO 9001:2008

Teletronics - A Curtiss-Wright Company  
 15 Terry Drive, Newtown, PA 18940  
 phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

[www.ttcdas.com](http://www.ttcdas.com)