

### Multimode Telemetry Demodulator



#### Applications

- Telemetry
- Compliance
- Field Training
- Simulation

#### Features

- Agile Data Rates 0.18 to 20 Mbps
- Demodulates SOQPSK and PCM/FM or Multi-symbol PCM/FM
- Intermediate Frequency of 70 MHz or 20 MHz
- Programmable Control, Local and Remote via IEEE-488 Bus
- Spectral Inversion Control
- Diversity Switch Support in All Modes
- RCC-106-04 Compatible
- Multi-symbol operation available as option

#### Description

The Model 2120-502 is a high-speed multi-mode demodulator designed to receive a family of modulation methods including SOQPSK and PCM/FM. It will yield low BER with the lowest possible C/N or corresponding  $E_b/N_0$  to optimize the range/distance and the quality of the received data. The Multi-symbol PCM/FM mode is available as an option. All modes provide the signals needed to support the RF Networks Model 2241 Diversity Branch Selector. The RF Networks Model 2120 operates without the need for a Bit Synchronizer or additional IF or RF filters and displays a robust bit error performance without the need for additional coding. This latest Model 2120 is the fourth generation of demodulator from RF Networks. All parameters are settable from the front panel or from the remote IEEE-488 bus.

Revision 05/07/2015

#### Model-2120-502 Datasheet

©2015 Teletronics - A Curtiss-Wright Company  
Specifications subject to change without notice.

Approved for Public Release 15-S-2024

Teletronics - A Curtiss-Wright Company  
15 Terry Drive, Newtown, PA 18940  
phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

[www.ttcdas.com](http://www.ttcdas.com)



Management  
System  
AS9100C  
ISO 9001:2008