

Airborne High Speed Fibre Channel Recorder



Features

- High Speed Data Recording
 - Up to 60 Megabytes/sec Data Recording Rate (line rate). Maximum rate is dependent on maximum recording rate of media within MSC Cartridge.
 - 1 Gigabit/sec Electrical Fibre Channel Interface
 - Supports Arbitrated Loop Connections
- Integrates One Media Storage Bay
- Available with Dzus mount or baseplate mounting
- Available with all black faceplate or Orange border
- Accepts MSC-XXXX Solid State Media Cartridges with capacities up to 384GBytes
- Uses Digital Recording Format
 - Supports SCSI Compatible Media Addressing
 - IRIG Chapter 10 Interface Compatible
- Ruggedized for Airborne Applications
- Discrete I/O Gives Recorder Status
- 28VDC Power Supply to support operation from Standard Aircraft Power

Description

The MSR-2001-PS airborne high speed recorder houses a single data cartridge which can record Fibre Channel data from the AIM-200X series of high-speed data acquisition and multiplexing units at a line rate of up to 100 Megabytes/sec (maximum data rates of approximately 32MB/sec when using a solid state media cartridge).

Applications

- High Speed Airborne Recording
- Replacement of Aging Tape-Based Data Recorders

Revision 09/17/2015

MSR-2001-PS Datasheet

©2015 Teletronics - A Curtiss-Wright Company
Specifications subject to change without notice.

Approved for Public Release 16-S-0987



CAIS
Compatible



Management
System
AS9100C
ISO 9001:2008

Teletronics - A Curtiss-Wright Company
15 Terry Drive, Newtown, PA 18940
phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com