

## Network-Based High-Speed Camera



### Applications

- Airborne separation testing
- Missile launch
- Ballistics testing
- Explosives testing
- Projectile tracking
- Component testing
- Vehicle testing
- Materials testing

### Features

- High resolution (1280 x 1024 pixels)
- High frame rate (up to 500 frames per second at full resolution)
- Provides RS-170A video with use of the nMGR-2000
- Rugged, lightweight and miniature size
- IEEE 1588 for time synchronization and timestamp support
- Circular buffer for pre-event and post-event image capture
- 100/1000BASE-T Ethernet
- Available with color or monochrome sensor

### Description

The TTC high-speed nHSC-36-S1(M)-1 camera design provides a unique solution for applications where space is at a premium, including airborne, automotive and ground testing.

The nHSC-36-S1(M)1 camera is a networked high-speed camera that is capable of 500 frames-per-second operation. The camera requires integration with nMGR-2000 camera manager to provide system configuration, download and storage of recorded frames, and video preview and post view. The camera easily integrates into a system with other TTC network equipment including network switches, recorders, the CCP-2X00 camera control panel and the nMGR-2000 high-speed camera manager.

The nHSC-36-S1(M)-1 camera is configured using TTCWare software and the recorded images can easily be extracted from the recording for data analysis.

Revision 01/24/2017

### nHSC-36-S1(M)-1 Datasheet

©2017 Teletronics - A Curtiss-Wright Company

Specifications subject to change without notice.

Approved for Public Release 17-S-0863

Teletronics - A Curtiss-Wright Company

15 Terry Drive, Newtown, PA 18940

phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

[www.ttcdas.com](http://www.ttcdas.com)



Management  
System  
AS9100C  
ISO 9001:2008