

### Solid State Recorder with Fixed Media up to 128 Gigabytes



#### Applications

- Airborne PCM/Parallel Data Recording
- Replacement of aging Tape Based Data Recorders

#### Features

- Solid State Data Recorder with Fixed Media
- Ruggedized for Airborne Applications
- Records PCM and IRIG Time or 8bit Parallel Data
- Smaller Form Factor than SMS-4000
- Multiple Mounting Options
- Records One Input Channel
  - PCM Data Rates up to 20Mbps
  - PCM Internal Frame Correlator
  - Parallel Data 20MBps Burst, 3MBps Sustained
- Uses Digital Recording Format
  - STANAG-4575 File Structure
- Flexible Control/Status Interfaces
  - RS-232 (Setup/Control/Status)
  - Discrete (Control/Status)
- USB 2.0 Download of Data
- IRIG-B Time Reader
  - Time Tag PCM Frames To 1 Microsecond Resolution

#### Description

The SMS-4002 solid state Data Recorder is used in demanding applications such as airborne instrumentation recording. The unit is configured to handle one high speed serial PCM input at data rates up to 20Mbps or 8 bit Parallel data at 20MBps burst with an average data rate of 3MBps. IRIG-B time also recorded when recording PCM data. A frame correlator decommutates the PCM data for direct word aligned data recording. Memory capacity ranging from 8GB to 128GB is available. The unit is programmable via serial RS-232. Control/Status is also provided. Acquired data can be downloaded via a USB 2.0 interface.

Revision 05/11/2015

#### SMS-4002 Datasheet

©2015 Teletronics - A Curtiss-Wright Company  
 Specifications subject to change without notice.

Approved for Public Release 16-S-1293



CAIS  
Compatible



Management  
System  
AS9100C  
ISO 9001:2008

Teletronics - A Curtiss-Wright Company  
 15 Terry Drive, Newtown, PA 18940  
 phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

[www.ttcdas.com](http://www.ttcdas.com)