

Solid State Recorder with Removable PCMCIA Memory Cards



Applications

- Flight Test Recording
- Limited Space Applications
- Portable Data Recording System
- Applications requiring Playback/Analysis on a Standard Laptop Computer

Features

- Solid State PCM/Recorder
- Works with CDAU/EDAU Systems
- Ruggedized for Airborne Applications
- Uses up to 2 PCMCIA Type II Cards
 - 2 Gbytes to 32 Gbytes per PCMCIA Media
 - Removable Data Transfer
- Acquires PCM within the EDAU/CDAU Bus
 - 100% PCM up to 10 Mbps
 - Select PCM Data
- Uses Digital Recording Format
 - Standard File Structure (FAT16 or STANAG 4575 Linear File Structure)
 - Microsecond Frame Time Tag
 - Simplifies Direct Analysis from Media
 - PCM Regeneration Not Required
- Flexible Control/Status Interfaces
 - RS-232 (Control/Status)
 - Discrete (Control/Status)

Description

The SSR-100L solid state PCM Recorder is used in demanding applications such as airborne instrumentation recording. The unit is configured to handle 100% PCM or select data at a rate up to 10 Mbps from within the EDAU/CDAU bus. PCM data is stored using direct file-structure recording. Plug-in PCMCIA cards are available with capacities ranging from 2 GB to 32 GB. The unit is programmable via serial RS-232. Control/Status is also provided. Acquired data can be analyzed/archived on a standard PC. File Format is backward compatible with older SSR-100 model.

Revision 05/11/2015

SSR-100L Datasheet

©2015 Teletronics - A Curtiss-Wright Company
 Specifications subject to change without notice.

Approved for Public Release 16-S-1303



CAIS
Compatible



Management
System
AS9100C
ISO 9001:2008

Teletronics - A Curtiss-Wright Company
 15 Terry Drive, Newtown, PA 18940
 phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com