

Airborne Multimode Transmitter, High Efficiency, C-Band



Features

- C Band
- Multimode Modulator
- Supports: PCM/FM, SOQPSK, & Multi-H CPM
- Frequency Selectable via RS-232 COM Port
- Provides IRIG compatible Randomizer
- Data Rates
 - PCM/FM from 80 kbps to 20 Mbps
 - Others Formats from 650 kbps to 40 Mbps
- Bit Rate Agile
- High Efficiency Power Amplifier Design
- 2.5" x 3.5" x 1.0"
- Environmentally Rugged

Description

TTC's TTS-9600 series Multimode Transmitter provides the user with state-of-the-art modulation compatibility to IRIG-106-04, with user programmability for center frequency and modulation options with a high efficiency power amplifier chain. The TTS-9670 series provides the highest power efficiency offered in the industry today while being backed by outstanding customer support.

Applications

- Missile Performance Testing
- Flight Test Instrumentation
- RPV Communications
- Remote Ground Communication
- Home Land Security

Options:

- IRIG Randomizer
- RS-422 Data interfaces
- RS-232/485 for Programming
- Internal Status for Temperature, Frequency
- Programmable Power Levels
- Custom Operating Frequency

Revision 05/07/2015

TTS-9600 Series Datasheet

©2015 Teletronics - A Curtiss-Wright Company
Specifications subject to change without notice.

Approved for Public Release 15-S-1866

Teletronics - A Curtiss-Wright Company
15 Terry Drive, Newtown, PA 18940
phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com



Management
System
AS9100C
ISO 9001:2008