

### Airborne Multimode Transmitter, High Efficiency, Dual L-Band



#### Applications

- Missile performance testing
- Flight test instrumentation
- RPV communications
- Space craft instrumentation
- Remote ground communication
- Home land security

#### Options:

- IRIG randomizer
- TTL or RS-422 data interfaces
- RS-232/422/485 for programming
- Internal status for temperature, frequency
- Programmable power levels
- Custom operating frequency

#### Features

- Dual L-Band
- Multimode modulator
- Supports: PCM/FM, SOQPSK, & Multi-H CPM
- Frequency Selectable via RS-232 COM port and Parallel BCD
- Provides IRIG compatible randomizer
- Data rates
  - PCM/FM from 80 kbps to 20 Mbps
  - Others Formats from 650 kbps to 40 Mbps
- Bit rate agile
- High efficiency power amplifier design
- 2.5" x 3.5" x 1.3"
- Environmentally rugged

#### Description

TTC's TTS-9660-2DL multimode transmitter provides the user with state-of-the-art modulation compatibility to IRIG-106-04, with user programmability provided through both a serial and parallel interfaces for center frequency and modulation options with a high efficiency power amplifier chain. The TTS-9660-2DL provides the highest power efficiency offered in the industry today while being backed by outstanding customer support.

Revision 08/17/2015

#### TTS-9660-2DL Datasheet

©2015 Teletronics - A Curtiss-Wright Company

Specifications subject to change without notice.

Approved for Public Release 16-S-1325

Teletronics - A Curtiss-Wright Company

15 Terry Drive, Newtown, PA 18940

phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

[www.ttcdas.com](http://www.ttcdas.com)



Management  
System  
AS9100C  
ISO 9001:2008