

Airborne Multimode Transmitter, High Efficiency



Applications

- Missile performance testing
- Flight test instrumentation
- RPV communications
- Space craft instrumentation
- Remote ground communication
- Home land security

Options:

- IRIG randomizer
- TTL or RS-422 data interfaces
- RS-232/422/485 BCD for programming
- Internal status for temperature, frequency
- Programmable power levels
- Custom operating frequency

Features

- C-BAND (BAND 2)
- Multimode modulator
- Supports: PCM/FM, SOQPSK, & Multi-H CPM
- Frequency Selectable via RS-232 COM port and Parallel BCD
- Provides IRIG compatible randomizer
- Data rates
 - PCM/FM from 80 kbps to 20 Mbps
 - Others Formats from 650 kbps to 40 Mbps
- Bit rate agile
- High efficiency power amplifier design
- 2.5" x 3.5" x 1.3"
- Environmentally rugged

Description

TTC's TTS-9690-2 series multimode transmitter provides the user with state-of-the-art modulation compatibility to IRIG-106-04, with user programmability provided through both a serial and parallel interfaces for center frequency and modulation options with a high efficiency power amplifier chain. The TTS-9690-2 series provides the highest power efficiency offered in the industry today while being backed by outstanding customer support.

Revision 08/28/2015

TTS-9690-2 Series Datasheet

©2015 Teletronics - A Curtiss-Wright Company
Specifications subject to change without notice.

Approved for Public Release 15-S-2552

Teletronics - A Curtiss-Wright Company
15 Terry Drive, Newtown, PA 18940
phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com



Management
System
AS9100C
ISO 9001:2008