


20 Mbps Wide-Band Data Acquisition Unit



Applications

- Stand-alone Data Acquisition
- Distributed Systems
- Vehicle Development
- CAIS Applications

Features

- High Speed Stand-alone Wide-Band Data Acquisition Unit
- Optional CAIS Remote Slave capability (RAM based acquisition-simultaneous with stand-alone function)
- Bit Rates up to 20 Mbps Operates at 8 through 16 BPW
- Programmable Formats and Sample Sequence
- External Simultaneous Sample capability
- Multiple unit can be rate and sample synchronized under control of:
 - CAIS Minor Frame
 - CAIS Major Frame
 - External Sample Clock
- 10-, 12- and 16 Slot Versions
- Plug-in overhead and signal conditioning cards
- Fully programmable with TTC's Windows XP/2000 Software Application
- Extremely Rugged Construction
- Fully programmable operation

Description

The WDAU-20XX is a CAIS compatible Wideband DAU for interfacing a variety of analog/digital Sensors. Encoded data is available in the PCM output data stream at up to 20 Mbps. The unit can be configured to simultaneously support selected data transfer to a Master encoder over the CAIS Bus, and to provide all acquired data in the PCM output. The unit includes various simultaneous sampling modes.

Revision 05/13/2015

WDAU-2010/12/16 Datasheet

©2015 Teletronics - A Curtiss-Wright Company
 Specifications subject to change without notice.

Approved for Public Release 16-S-1361



CAIS
Compatible



Management
System
AS9100C
ISO 9001:2008

Teletronics - A Curtiss-Wright Company
 15 Terry Drive, Newtown, PA 18940
 phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com