

C-Band Non-Coherent Radar Transponder



Applications

- Instrumentation tracking Radar
- Range Expansion/Enhancement
- UAVs, Target Drones, Missiles & Aircraft

Features

- 20 Watt minimum pulse output power
- Sensitive Super-Heterodyne receiver
- Independent Transmit and Receive frequency Agility
- Small form factor, under 17 cubic inches
- Low weight, under 16 ounces (454 grams)
- Frequency Agile over 5.4 to 5.9 GHz
- Reverse polarity power lead protection
- Selectable code spacing
- Selectable reply delay
- Internal duplexer for single antenna operation
- Mismatch protection from high Antenna VSWR
- IRIG 262-02 compliant

Description

The XPDR-2020/2050 Radar Transponder is an ultra-miniature, 20/50 Watt module used to enhance the capability of C-band radars. The highly integrated design of these modules make them desirable for those applications where size, weight, and DC input power are at a premium. This module is intended for UAV's, compact missiles, and any other platform that requires a premium performance transponder with minimal space and weight allocations. The XPDR-2020/2050 incorporates in its design, the state of the art in power, RF, and digital devices and circuitry. This modern design lends itself to a high reliability, high MTBF module.

Revision 05/07/2015

XPDR-2020/2050 Datasheet

©2015 Teletronics - A Curtiss-Wright Company
Specifications subject to change without notice.

Approved for Public Release 15-S-1976

Teletronics - A Curtiss-Wright Company
15 Terry Drive, Newtown, PA 18940
phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com



Management
System
AS9100C
ISO 9001:2008